



## DOWNLIGHT / HOLLOW-S

Ürün Kodu Product Code	Çalışma Voltajı (V) Operating Voltage (V)	CRI CRI	Işık Akısı (lm/mt) Luminous Flux (lm/mt)	Güç (W/mt) Power (W/mt)	Ölçüler (cm) Dimensions (cm)	Delik Ölçüsü (cm) Cut Out (cm)
HOLLOW-S 1	220V AC	>80	750	6	D 7 x W 9.7 x H 9.7	8.5
HOLLOW-S 2	220V AC	>80	750	6	D 7 x W 11.7 x H 11.7	10.5
HOLLOW-S 3	220V AC	>80	1000	8	D 7.5 x W 14.7 x H 14.7	13
HOLLOW-S 4	220V AC	>80	1500	12	D 8.5 x W 17.5 x H 17.5	16
HOLLOW-S 5	220V AC	>80	2000	16	D 8.5 x W 19.2 x H 19.2	17.5
HOLLOW-S 6	220V AC	>80	3000	25	D 8.5 x W 22.7 x H 22.7	21

### Aksesuarlar Accessories

PCB  
Con.



IP20  
Con.



IP67  
Con.



### Işık Açısı Light Angle

120°

### Renk Color



### Kullanım Alanları Usage Areas



### Kontrol Sistemleri Control Systems

